



TIGHTLOCK NETTING



Tightlock Netting is New Zealand’s most trusted prefabricated fence.

SUITABLE FOR ALL HIGH PRESSURE STOCK APPLICATIONS.

Tightlock netting is manufactured using zinc/alloy coated 2.5mm wire for long life. Tightlock’s knot technology and wire spacings provide economical permanent fencing solutions for deer, sheep and beef applications.

A Kiwi trusted, high quality fence Eclipse’s Tightlock fence consists of line, stay and knot wires. Line wires are continuous in length and made from high tensile wire. The stay wires (vertical) are made from medium tensile wire and continuous in length. They combine with the knots and tension curves to create overall rigidity and elasticity. The knots are made from low tensile wire and can hold between 60-90kg per knot. The load of any impact will spread and dissipate over the full fence height and for some distance on either side.

Applications	
Fawn	Used in deer fawning paddocks due to the tighter 240 mm stay wire combined with the 89 mm line wire prevents newborn fawns from slipping through the fence.
Deer	1550mm and 1900mm heights available for traditional deer applications.
Top Up	Used to add height to existing fence as required instead of replacing the entire fence.

Size Range Available					
Type	Description	Line Wires	Roll Height (mm)	Stay Spacing Width (mm)	Length (m)
Fawn	A16 / 1900	16	1900	240	100
Deer	A13 / 1900	13	1900	150 / 300	100
	A11 / 1550	11	1550	150 / 300	100
Top Up	A5 / 900	5	900	300	200
	A5 / 600	5	600	300	200
Field	A8 / 900	8	900	150 / 300	50 / 100
	A8 / 800	8	800	300	50 / 100
	A7 / 900	7	900	150 / 300	50 / 100

Eclipse fencing is manufactured by United Wire Products and meets the WIREMARK® Quality Standard.

Freephone: 0800 333 188
www.unitedwire.co.nz

