

# TWINLOCK FABRICATED FENCE



SINCE 1903




## Twinlock netting is New Zealand's most trusted prefabricated fence.

**Twinlock netting provides farmers with a fast and cost-effective solution for temporary and permanent stock control.**

Suitable for low and medium pressure applications. Twinlock netting is manufactured using zinc/aluminium alloy coated wire for long life and is available in 2.00mm and 2.50mm wire diameters.

A versatile, easy-to-install prefabricated fence, Twinlock uses a continuous knot to securely join the line and stay wires, creating a flexible fence that is well suited to a wide range of rural applications. Available in Field, Light and Soft configurations, Twinlock can be used for sheep, cattle and goats, conservation and forestry blocks, low-pressure lifestyle and residential fencing, as well as electrified break feeding and lamb docking applications.



| Applications |                                                       |
|--------------|-------------------------------------------------------|
| <b>Field</b> | Sheep, cattle, goats, conservation and forestry block |
| <b>Soft</b>  | Can be electrified break feeding. Lambs / docking     |
| <b>Light</b> | Low stock pressure, lifestyle and residential fences  |

| Size Range Available |             |            |                  |                         |            |
|----------------------|-------------|------------|------------------|-------------------------|------------|
| Type                 | Description | Line Wires | Roll Height (mm) | Stay Spacing Width (mm) | Length (m) |
| <b>Field</b>         | B8/900      | 8          | 900              | 150                     | 50 / 100   |
| <b>Light*</b>        | BL7/900     | 7          | 900              | 300                     | 50 / 100   |
|                      | BL8/900     | 8          | 900              | 150                     | 50 / 100   |
|                      | BL8/900     | 8          | 900              | 300                     | 100        |
| <b>Soft**</b>        | B5/525      | 5          | 525              | 150                     | 100        |

\* Light uses a 2.00 mm high tensile wire for the line wire.

\*\* Soft uses a low tensile wire for the line wire.

Cyclone fencing is manufactured by United Wire Products and meets the WIREMARK® Quality Standard.

Freephone: 0800 333 188  
www.unitedwire.co.nz

