

FENCING WIRE



SINCE 1903



Cyclone offers an extensive range of fencing wire to suit any application.

All high tensile Hispan life products contain Vanadium for improved malleability and feature 2 life or 4 life zinc/alloy coating for superior durability in corrosive environments. A range of low tensile wire is available for traditional fencing applications.



Hispan 2 Life

For general farming and industrial applications, with a Zinc/Alloy coating that delivers two times the life of heavy galv wire.

Hispan 4 Life

For coastal and high corrosion conditions, with a heavy Zinc/Alloy coating that delivers four times the life of galvanised Hispan.

Soft lacing wire is available in 1.60, 2.00 and 2.50mm diameters.

Lacing Needles are available in 1.60 and 2.00mm diameters.

Low Tensile	
HiSPAN	DIAMETER (mm)
2 Life	1.60mm, 2.00mm, 2.50mm, 3.15mm, 4.00mm
4 Life	3.15mm, 4.00mm

High Tensile	
HiSPAN	DIAMETER (mm)
2 Life	1.60mm, 2.00mm, 2.50mm, 3.15mm, 3.55mm, 4.00mm
4 Life	2.50mm, 3.15mm

Manufactured and tested to New Zealand Fencing Standard NZS3471:1974 and Coating Standard AS/NZS 4534/ W05Z5A. Carries the WIREMARK Guarantee. New Zealand made.

Cyclone fencing is manufactured by United Wire Products and meets the WIREMARK® Quality Standard.



Freephone: 0800 333 188
www.unitedwire.co.nz

